

Standard panel 19 mm

Description	Material / Finish	Thickness in mm	kg/m ²	Density/m ³
Front	LightBeton	1,5	2,25	1500
Carrier	MDF flame retardant	16	10,50	660
Back	LightBeton, RS quality	1,5	2,25	1500
	Composite panel	19	15,00	
Fire protection	Consolidated certification B-s2, d0			

Flexline 4 mm

Description	Material / Finish	Fire protection	Thickness in mm	kg/m ²	Density/m ³
Front	LightBeton	B-s2, d0	1,5	2,25	1500
Carrier	Flex-Mineral sheet	Bfl-s1	2,5	4,40	1760
	Composite panel		4	6,65	

Features of concrete surface

Description	Standard	Stress group	Remark
Abrasion resistance	DIN 68861-2	2A	High abrasion resistance
Scratch resistance	DIN 68861-4	4E	Fits worktop requirements
Resistance to fading	DIN 15187	<6	Blue-scale
Fire behavior	DIN EN 13501-1	B-s2, d0	Flame retardant
Concrete sealing	Two-component acrylic matt lacquer, water-based		

Dimensions - all specifications in mm

Description	Length	Width	Thickness	PU Pallet	PU kg
Standard panel (Untrimmed sizes +/- 5)	3020	1250	19	25	1650
Flexline (Untrimmed sizes without bevel +/- 5)	2650/2050	1020/1250	4	Order-related	
Flexline (Custom sizes with bevel +/- 0,3)	1000/1200	500/600	4	Order-related	
Concrete pure (Untrimmed sizes +/- 5)	3020	1250	1,5	Order-related	
Formwork (Custom sizes +/- 0,3)	2000	1200	19	Order-related	
Formwork (Custom sizes +/- 0,3)	1000	1200	19	Order-related	
Formwork (Custom sizes +/- 0,3)	600	1200	19	Order-related	

Pores, hairline fractures and colour fluctuations are characteristic features of concrete. They do not therefore constitute grounds for complaint.

Our technical recommendations relating to the application, both spoken and written, provided by us in support of the buyer/processor, based on our experience and in line with the facts as currently known in science and in practice, are non-binding and do not establish any contractual legal rights nor any collateral obligations arising out of the purchase agreement. They do not release the buyer from his/her duty to check for him/herself as to whether our products are suitable for the intended purpose.